

RUGGED TABLET PC μTACT

Technical Specifications

μTACT military

10,4 inch – Industrial Version page (1/2)



Display:

- Sunlight readable 10,4 inch touchscreen (400 cd/m2)
- 800 x 600 Resolution (SVGA)

Pointing System:

- Resistive touchscreen (efficient with gloves and any kind of pen)
- Mouse joystick system (option)
- 2 configurable buttons in front face

External keyboard (option):

- Environment Sealed IP65

Operating System:

- Windows XP Embedded
- Specific menu or standard Windows interface

Processor / Memory / Hard Disk:

- Pentium III Celeron 700 MHz
- 256 Mb RAM
- 512 Mb Compact Flash Hard Disk (expandable to 4 Gb)

Expansion:

- 1 USB port
- 1 Ethernet 10/100 Mbps port
- 1 IRDA 1.1 (4Mbps) port
- 1 PCMCIA port (type 1 or 2)

Civil GPS (option):

- Internal GPS receiver (NMEA protocol)

μTACT industrial



RUGGED TABLET PC μTACT

Technical Specifications

μTACT military

10,4 inch – Industrial Version page (2/2)



Power supply:

- 2 hot-plugged Li-Ions batteries
- Autonomy: 5 hours
- AC/DC Power Adapter/Charger
- Charge in 2h30
- Charge indicator and low battery alarm

Reliability:

- MTBF > 10000 H

Environment:

- Operating Temperature: -25°C +55°C
- Storage Temperature: -40°C +70°C
- IP66 Rating

Accessories:

- AC/DC Power Adapter/Charger
- Configuration Software
- User Manual
- Windows XP Embedded license

Dimensions and weight:

- 273 mm x 288 mm x 75 mm
- 4 Kg with 2 batteries
- 3,3 Kg without battery

Norm:

- Shocks and vibrations: EN 60068-2
- EMI : EN 61000-6-2
- CE

μTACT industrial

